

Genie® IWP™ -20S, IWP-25S, IWP-30S

Specifications

Models	IWP-20S		IWP-25S		IWP-30S	
	US	Metric	US	Metric	US	Metric
Working height max. ⁽¹⁾	26 ft 3 in	8.17 m	30 ft 11 in	9.60 m	35 ft 6 in	11 m
Platform height	20 ft 3 in	6.17 m	24 ft 11 in	7.60 m	29 ft 6 in	9 m
Ⓐ Horizontal outreach ⁽²⁾	2 ft 2 in	0.61 m	-	-	-	-
Ⓑ Height - stowed, fully lowered	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m
Ⓑ Height - stowed, base raised	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
Ⓒ Length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
Ⓓ Width - standard base	2 ft 8 in	0.81 m	2 ft 8 in	0.81 m	-	-
Ⓓ Width - wide base	-	-	-	-	3 ft 4 in	1.02 m
Corner access ⁽³⁾	6 in	15 cm	6 in	15 cm	7 in	18 cm

Productivity

Lift capacity	350 lb	159 kg	350 lb	159 kg	350 lb	159 kg
Lift capacity, with outreach option	300 lb	136 kg	-	-	-	-
Standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gate standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated narrow	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm
Standard fiberglass ⁽²⁾	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm

Power

Power source - AC models	110V/50-60 Hz	110V/50-60 Hz	110V/50-60 Hz
	220V/50-60 Hz	220V/50-60 Hz	220V/50-60 Hz
Power source - DC models	12V DC	12V DC	12V DC

Weight and Floor Loading⁽⁴⁾

Standard base - AC	1,245 lb	564 kg	1,290 lb	585 kg	-	-
Standard base - DC	1,345 lb	610 kg	1,390 lb	630 kg	-	-
Standard base with outreach option - AC	1,350 lb	612 kg	-	-	-	-
Standard base with outreach option - DC	1,450 lb	658 kg	-	-	-	-
Wide bas - AC	-	-	-	-	1,430 lb	649 kg
Wide bas - DC	-	-	-	-	1,530 lb	694 kg
Occupied floor pressure	0.92 psi	2.40 kPa	0.28 psi	1.90 kPa	0.82 psi	5.64 kPa

Sound and Vibration Levels

Sound Pressure level (ground workstation)	< 70 dBA		< 70 dBA		< 70 dBA	
Sound Pressure level (platform workstation)	< 70 dBA		< 70 dBA		< 70 dBA	
Vibrations	< 8 ft 2 in/s ²	< 2.5 m/s ²	< 8 ft 2 in/s ²	< 2.5 m/s ²	< 8 ft 2 in/s ²	< 2.5 m/s ²

(1) The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

(2) Horizontal outreach option available only on the IWP-20S, not available with fiberglass platform

(3) Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

(4) Weight will vary depending on options and/or country standards.

(5) Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.

Genie® IWP™ -20S, IWP-25S, IWP-30S

SKU: Stock Models

- IWP-20S, AC Power*
- IWP-25S, AC Power*
- IWP-30S, AC Power, Wide base*

* Build to Order

SKU: Stock Models

- **IWP20S01AE0001:** IWP-20S, DC Power
- **IWP25S01AE0001:** IWP-25S, DC Power
- **IWP30S01AE0001:** IWP-30S, DC Power, Wide base

Option availability	S	S+	BtO	
Power	AC85V power		<input type="radio"/>	
	AC110V power		<input type="radio"/>	
	AC220V power		<input type="radio"/>	
	DC Power	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Dry battery (DC)		<input type="radio"/>	<input type="radio"/>
	Wet battery (DC)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Dual battery package (DC)		<input type="radio"/>	<input checked="" type="checkbox"/>
	Power wheel assist with dual battery package			<input type="radio"/>
	12V 110/230V 50-60Hz worldwide smart charging system	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Platform	Sliding mid-rail standard platform	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Gated standard platform				<input type="radio"/>
Gated narrow platform				<input type="radio"/>
Standard fiberglass platform				<input type="radio"/>
Descent light and alarm package				<input type="radio"/>
Tool tray				<input type="radio"/>
AC power to platform		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Chassis		Long cord 79"		<input type="radio"/>
	Auxiliary platform lowering	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Built in leveling system	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Crane attachment point	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Dual activated up/down switch	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Easy operation: rolls through standard doorways	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Forklift pockets (Standard base only)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Ground fault interrupt	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Heavy-duty design and mast	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Tie-down attachment points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Power wheel assist dimensions (Length: +12.5in/+32cm - Weight: +285lb/129kg)

- S Standard
- S+ Standard +
- BtO Build to Order
- Standard Features
- Options



Quick Setup



Compact Footprint



Low Floor Loading



Genie Genuine Accessories⁽¹⁾

- Platform-locating laser light
- Fluorescent tube caddy

(1) More accessories available from Genie Genuine Parts.

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Xtra Capacity, Lift Power, Lift Guard, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries.

Updated 11/21



A TEREX BRAND
© 2021 Terex Corporation

